


Set of radio relay RR4702 – ordering information

Basic set of RR4702:

<i>Ordering number</i>	<i>Preview</i>	<i>Description</i>	<i>Notice</i>
RR47-IDU0-02M		indoor unit IDU RR4702 ETH100/1000, E1, MNGMT, USB	
RR47-ODU1-02M		outdoor unit ODU1 RR4702 sub-band I a III	
RR47-ODU2-02M		outdoor unit ODU2 RR4702 sub-band II a IV	
RR47-AAEL-000		holder of antenna and ODU - elevation < 3kg, ± 25°, Ø 40mm	option below: statical holder
RR47-FA26-GRE		flat panel antenna green color 26 dBi, 6°, 600x600x24mm, 5 kg, H or V turn 90°	option below: antenna tan color
RR47-CAOD-000		ODU – antenna cable 0.8 m, N – N90	
RR00-MICR-000		hand-microtelephone micr.+ repr. + PTT	
Documentation		User's guide Software manual CD with drivers	

Accessories and options:

<i>Ordering number</i>	<i>Preview</i>	<i>Description</i>	<i>Notice</i>
RR47-CIOD-XXX		IDU-ODU cable type of connectors and length of cable are specified by XXX	XXX: 050 – 50m, N,N 059 – 50m, N,N90 100 – 100m, N,N 109 – 100m, N,N90 150 – 150m, N,N 159 – 150m, N,N90 200 – 200m, N,N 209 – 200m, N,N90 300 – 300m, N,N 309 – 300m, N,N90
RR47-DIOD-XXX		IDU-ODU cable drums size of drums is specified by XXX	XXX: 200 – to 200m 500 – over 200m
RR00-CUSB-000		USB cable A-A, 1.8 m	
RR00-CPWR-XXX		Power cable length of cable is specified by XXX	XXX: 003 – 3m 005 – 5m 010 – 10m
RR00-GDTF-000		lightning protection fuse (2 pieces per radio)	
RR47-AAST-000		holder of antenna and ODU - statical < 2kg, Ø 40mm	
RR47-FA26-TAN		flat panel antenna tan color 26 dBi, 6°, 600x600x24mm, 5 kg, H or V turn 90°	

RR47-PA29-GRI		grid parabolic antenna 29 dBi, Ø 1m, 6 kg,	
RR47-PA27-000		solid parabolic antenna 27 dBi, Ø 0.77m, 5,2 kg,	
RR00-ACDC-000		power supply AC/DC AC 100-275V -> DC 28V/40A	
RR00-DCDC-000		power supply DC/DC DC 12V -> DC 28V/30A	
RR00-ADDC-000		power supply AC, DC/DC AC 100-275V, DC 12V -> DC 28V/40A	
RR00-MAST-XXX		mast parameters of mast are specified by customer	